

DZ47(C45N) MINI CIRCUIT BREAKER



1P

2P

3P

4P

APPLICATION

DZ47-63(C45N) series circuit breaker is used in lighting distribution system or motor distribution system for protecting overload and short-circuit in the system. The product is neoteric in structure, light in weight, reliable and excellent in performance. Its frame and parts adopt plastics of high fire-resistant and shockproof. The product, with long life, is mainly used in AC 50Hz/60Hz single-pole 240V or two, three, four pole 415V circuit for overload and short-circuit protection as well as for unfrequent on-and-off switching electric equipment and lighting circuit in normal case. The products comply with IEC898&BS3871 standards.

SPECIFICATION

Standard	Rated current(A)	Pole	Voltage(V)	Breaking capacity(A)
BS3871-1 IEC60898	1 to 40	1	240	6000
		2,3,4	415	6000
	50 to 63	1	240	4000
		2,3,4	415	4000
1	1	1	220/240	10000
		2,3,4	220/240	20000
		2,3,4	380/415	10000
3	3	1	220/240	8000
		2,3,4	220/240	20000
		2,3,4	380/415	8000
IEC157-1	10 to 40	1	220/240	7000
		2,3,4	220/240	16000
		2,3,4	380/415	8000
50	50	1	220/240	6000
		2,3,4	220/240	10000
		2,3,4	380/415	6000
63	63	1	220/240	5000
		2,3,4	220/240	10000
		2,3,4	380/415	5000

DIMENSIONS

